

## TO: OUR CUSTOMERS

Our construction methods offer many quality and time saving advantages.

## S-P PRODUCTS, INC. EZ PULL/EZ READ WIRING HARNESS

### SPECIFICATION SHEET

#### EACH HARNESS:

1. To be UL Listed as a complete assembly.
2. Each wire to be printed every ½” along its entire length with any combination of numbers and/or letters up to 64 characters including spaces. Common neutrals and grounds can be labeled per above to show all the circuits they pertain to and therefore aid the contractor when trouble shooting.
3. Wires to be bound together by PVC Cross Tape Only Method with easy to remove tabs to enable the conductors to flow separately and freely into the conduit or wire-way. No tape or lacing remains to create a stiff, difficult to pull harness or to be snagged, cut and balled-up during the pull.
4. Trees with looped phase wires and neutrals and break-outs are available wherever needed in the harness according to the customers’ exact dimensions required.
5. 360 degrees of both inside flanges of reel to be completely covered along their rim with smooth fiber glass tape to prevent conductors from being snagged or cut during the pull.
6. All conductors to run straight or parallel to allow fast break-out and termination.
7. Harnesses to be delivered on truck with hydraulic lift gate. Small reels can be grouped and palletized laying flat and stacked. Larger reels to be shipped upright so they can easily be rolled from the truck.
8. To have a 4” tall IBEW Union Label on one outer flange.

