

# Prefab Assemblies for Data Power Distribution Units



Any Manufacturers' brand, type and configuration of UL Listed components

Cables Satisfy National Electrical Code Article 645.5(E) and do not have to be securely fastened in place and supported every 4.5 feet as stated in article 350.30(A).

Every assembly is carefully and thoroughly tested per customers' requirements for ground integrity, insulation leaks, proper phase rotation and all conductors are Hi-Pots tested at twice rated circuit voltage plus 1,000 volts.

Certificate of calibration provided with each order.

Assemblies are marked at each end with custom labels protected by clear heat shrink tubing to prevent alteration or accidental removing.

Liquidtight conduit colors available in: black, gray, blue, red, yellow, green, orange, brown, and white up thru 225 ft.

Specify all components and if certain manufacturers' brands are required

Single or multiple circuits provided.



Consult factory for prices and availability.

**Customer must satisfy all codes and owners' specifications.**



PATENT PENDING  
PATENTED



LABELS APPLY TO PRODUCTS ONLY WHERE SHOWN ABOVE

730 Pratt Boulevard • Elk Grove Village, IL 60007  
P: (847) 593-8595 • F: (847) 593-8629 • Toll-free (800) 233-8595  
E: info@spproducts.com • www.spproducts.com

**PFA1**